

Power Optimiser For Australia

P650 / P730 / P801 / P850 / P800p / P950



POWEROPTIMISER

PV power optimisation at the module-level

The most cost effective solution for commercial and large field installations

- Specifically designed to work with SolarEdge inverters
- Up to 25% more energy
- Superior efficiency (99.5%)
- Balance of System cost reduction; 50% less cables, fuses and combiner boxes, over 2x longer string lengths possible
- Fast installation with a single bolt
- Advanced maintenance with module-level monitoring
- Module-level voltage shutdown for installer and firefighter safety
- Use with two PV modules connected in series or in parallel

/ Power Optimiser

For Australia

P650 / P730 / P801 / P850 / P800p / P950

Optimiser Model (Typical Module Compatibility)	P650 (for 2 x 60-cell PV modules)	P730 (for 2 x 72-cell PV modules)	P801 (for 2x72- cell PV modules)	P850 (for 2x high power or bi- facial modules)	P800p (for 2x 96- cell 5" PV modules)	P950 (for 2x high power or bi- facial modules)		
INPUT								
Rated Input DC Power ⁽¹⁾	650	730	800	850	800	950	W	
Connection Method	Single input for series connected modules				Dual input for independently connected ⁽⁷⁾	Single input for series connected modules		
Absolute Maximum Input Voltage (Voc at lowest temperature)	96	125			83	125	Vdc	
MPPT Operating Range	12.5 - 80	12.5 - 105			12.5 - 83	12.5 - 105	Vdc	
Maximum Short Circuit Current per Input (Isc)	11			12.5	7	12.5	Adc	
Maximum Efficiency	99.5						%	
Weighted Efficiency	98.6						%	
Overvoltage Category	II							
OUTPUT DURING OPERATION (POWER OPTIMISER CONNECTED TO OPERATING SOLAREEDGE INVERTER)								
Maximum Output Current	15			18		17	Adc	
Maximum Output Voltage	85						Vdc	
OUTPUT DURING STANDBY (POWER OPTIMISER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)								
Safety Output Voltage per Power Optimiser	1 ± 0.1						Vdc	
STANDARD COMPLIANCE								
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3							
Safety	IEC62109-1 (class II safety)							
RoHS	Yes							
Fire Safety	VDE-AR-E 2100-712:2013-05							
INSTALLATION SPECIFICATIONS								
Compatible SolarEdge Inverters	Three phase inverters SE15K & larger			Three phase inverters SE16K & larger				
Maximum Allowed System Voltage	1000						Vdc	
Dimensions (W x L x H)	129 x 153 x 42.5	129 x 153 x 49.5		129 x 162 x 59	129 x 168 x 59	129 x 162 x 59	mm	
Weight (including cables)	834	933		1064			gr	
Input Connector	MC4 ⁽²⁾							
Output Connector	MC4							
Output Wire Length	2.2						m	
Input wire length	0.16	0.16, 0.9 ⁽³⁾		0.16, 0.9, 1.3, 1.6 ⁽³⁾	0.16	0.16, 1.3, 1.6 ⁽³⁾	m	
Operating Temperature Range ⁽⁴⁾	-40 - +85						°C	
Protection Rating	IP68 / NEMA6P							
Relative Humidity	0 - 100						%	

⁽¹⁾ Rated power of the module at STC will not exceed the optimiser "Rated Input DC Power". Modules with up to +5% power tolerance are allowed.

⁽²⁾ For other connector types please contact SolarEdge.

⁽³⁾ Longer inputs wire length are available for use with split junction box modules (For 0.9m order P730-xxxLxxx or P801/P850-xxxLxxx. For 1.3m order P850-xxxYxxx or P950-xxxYxxx. For 1.6m order P850-xxxYxxx or P950-xxxYxxx).

⁽⁴⁾ For ambient temperature above +70°C power de-rating is applied. Refer to Power Optimisers Temperature De-Rating Technical Note for more details.

PV System Design Using a Solaredge Inverter ⁽⁵⁾⁽⁶⁾⁽⁷⁾		Three Phase SE15K and larger						Three Phase for 277/480V grid						
Compatible Power Optimisers		P650	P730	P801	P850	P800p	P950	P650	P730	P801	P850	P800p	P950	
Minimum String Length	Power Optimisers	14												
	PV Modules ⁽⁷⁾	27												
Maximum String Length	Power Optimisers	30												
	PV Modules ⁽⁷⁾	60												
Maximum Power per String		11250 ⁽⁸⁾		13500 ⁽⁸⁾		12750 ⁽⁸⁾	12750 ⁽⁹⁾			15300 ⁽⁹⁾		14450 ⁽⁹⁾		W
Parallel Strings of Different Lengths or Orientations		Yes												

⁽⁵⁾ P650/P730/P801 can be mixed in one string. It is not allowed to mix P650/P730/P801 with P850/P800p. It is not allowed to mix P950 with any other power optimiser or to mix P650-P950 with P300-P505 in one string.

⁽⁶⁾ For SE15K and above, the minimum DC power should be 11KW.

⁽⁷⁾ In a case of odd number of PV modules in one string it is allowed to install one P650/P730/P850/P800p/P801/P950 power optimizer connected to one PV module. When connecting a single module to the P800p seal the unused input connectors with the supplied pair of seals.

⁽⁸⁾ For the 230/400V grid: with P650/P730/P801 up to 13,500W per string may be installed, with P850/P800p up to 15,750W and with P950 up to 16,250W per string may be installed when the maximum power difference between each string is 2,000W

⁽⁹⁾ For the 277/480V grid: with P650/P730/P801 up to 15,000W per string may be installed, with P850/P800p up to 17,550W and with P950 up to 17,950W per string may be installed when the maximum power difference between each string is 2,000W